



The SLI Model 1260 provides a durable, reliable, and portable light and power source for any situation or environment. The towers are outfitted with a photo sensor that controls light on/off times, thus eliminating any operator interaction. Heavy duty construction allows use of this tower in virtually any environment where portable lighting is required.

#### **Key Performance Features**


- Rapid set up time
- 2000w - 120 volt auxillary power receptacle
- 20 hour continuous-run battery capacity with no charging
- 4-point retractable stabilizers/out-riggers
- NO sound or emissions
- Unit can be charged from 120 volt receptacle
- Removable tongue hitch

#### **Cost Effective**



- Solar charging capacity uses the suns energy to charge batteries
- Timer & photo sensor functions allow use with NO daily operator interaction
- NO fuel required
- AGM batteries require NO maintenance



Solar Lighting International, Inc.  
Phone 803-233-3461  
[www.solarlightingintl.com](http://www.solarlightingintl.com)



**Transport Position**



**Deployed Position**


## SLI 1260 Solar Light Tower

<b>Solar Modules</b>	4 325 Watt
<b>AGM Batteries</b>	6 260 A/Hr
<b>LED Lights</b>	1 100 Watt Tunnel & 2 200 Watt Flood
<b>Inverter/Charger</b>	1 60 AMP AC Charger
<b>Inverter</b>	1 Pure Sine 2000 Watt
<b>Charge Controller</b>	2 60 AMP Charge Controllers
<b>Light Stand</b>	22' Fixed Mast
<b>Trailer</b>	3500 lb Axle, 4" Channel, 2" Ball hitch, 2640 total weight



All electrical components are UL listed.

### 2 Year Workmanship Warranty

Manufacturer's warranty is limited to defective workmanship and failure to routine use according to manufacturer's operating guidelines. Warranty does not cover failure as a result of abuse, neglect, or misuse of this product.



**Transport Position**



**Deployed Position**

## SLI 1260 Solar Light Tower

<b>Solar Modules</b>	4 325 Watt
<b>AGM Batteries</b>	6 260 A/Hr
<b>LED Lights</b>	1 100 Watt Tunnel & 2 200 Watt Flood
<b>Inverter/Charger</b>	1 60 AMP AC Charger
<b>Inverter</b>	1 Pure Sine 2000 Watt
<b>Charge Controller</b>	2 60 AMP Charge Controllers
<b>Light Stand</b>	22' Fixed Mast
<b>Trailer</b>	3500 lb Axle, 4" Channel, 2" Ball hitch, 2640 total weight

All electrical components are UL listed.

### 2 Year Workmanship Warranty

Manufacturer's warranty is limited to defective workmanship and failure to routine use according to manufacturer's operating guidelines. Warranty does not cover failure as a result of abuse, neglect, or misuse of this product.